

**Product: Decca BridgeMaster E Series Radars**

**Subject: Vision FT BridgeMaster E 340 Displays**

Marketing Information Bulletin No. 69 recently published announced the introduction of the latest version of flat screen BridgeMaster E 340 Displays to be known as Vision FT BridgeMaster E 340 Radar Systems.

This document is a Technical supplement to it.



➤ **Spares**

Additional to the normal BME spares, you should be aware of the following new items:

T65923C Flat Panel Display  
T65900605 Trackerball (serial)  
T65900622 On/Off Switch

➤ **Access to Trackerball or Keyboard**

To replace the Trackerball or the Keyboard you will have to first remove the panel supporting them. To do this, first remove the two M4 Cap Head bolts at either end underneath the tray. Then remove the three M4 nuts through recessed holes underneath the tray. Lift the panel from the front edge and slide towards you. The Keyboard or the Trackerball can now be replaced.

➤ **Access to Flat Panel Display**

To replace the Flat Panel Display, removal is as follows. First remove the four M6 Cap Head bolts at each corner. The top two holes are threaded to take M8 bolts. Carefully screw in a bolt (e.g. M8 x 25) at each corner. Pull the bolts towards you bringing the FPD into a vertical position. You can now remove the cables before lifting the unit away.

➤ **65923680 Shelf Kit**

If required an Optional 'Shelf Kit' could be purchased. This can then be used to support a 2 x 4 Way Interswitch or TCU etc.

*Note: Suitable holes will have to be drilled to secure the additional unit.*